INTERNAL TOOTH LOCKWASHER
MS35333 or AN936A

EXTERNAL TOOTH LOCKWASHER
MS35335 or AN936B

Steel - Cadmium Plated per QQ-P-416, Type II, Class 2
Corrosion Resistant Steel - 410H Stainless

MS35333 Steel	AN936A	MS35333 CRES	Screw or Bolt Size	MS35335 Steel	AN936B	MS35335 CRES
-35	2	**-69**	#2	**-**	-	**-**
-36	4	**-70**	#4	**-29**	4	**-57**
-37	6	**-71**	#6	**-30**	6	**-58**
-38	8	**-72**	#8	**-31**	8	**-59**
-39	10	**-73**	#10	**-32**	10	**-60**
-40	416	**-74**	1/4	**-33**	416	**-61**
-41	516	**-75**	5/16	**-34**	516	**-62**
-42	616	**-76**	3/8	**-35**	616	**-63**
-43	716	**-77**	7/16	**-36**	716	**-64**
-44	816	**-78**	1/2	**-37**	816	**-65**
Sizes continue to 1-1/4 inch I.D.				Sizes continue to 1 inch I.D.		

*Prices for MS35333 parts only. MS35335 run higher.

FINISHING WASHER

Countersunk
MS27129 NAS391 #601
Brass - Nickel Plated per QQ-N-290 or Chromium Plated per QQ-C-320
Stainless - 300 Series 18-8

Flush
NAS390 #603
Brass - Nickel Plated per QQ-N-290 or Chromium Plate per QQ-C-320

MS27129 Brass	NAS391B Brass	#601 Brass	MS27129 Stainless	Screw Size	NAS390B Brass	#603 Brass
-1	4P	-4	-3	**#4**	4P	-4
-4	6P	-6	-6	**#6**	6P	-6
-7	8P	-8	-9	**#8**	8P	-8
-10	10P	-10	-12	**#10**	10P	-10



Note: Both washer types may be used with 82 or 100 degree countersunk screws.

100 DEGREE DIMPLED (TINNERMAN) WASHER

Spring Steel - Heat Treated, Cadmium Plated
Stainless - 300 Series - High Luster Polished

Screw or Bolt Size	OD	ID	T	PART#	TINNERMAN#	STAINLESS PART#	TINNERMAN#
#6	.50	.140-.147	.012	**DP1075-12**	A3235-012-24A	**DP1075-12SS**	
#8	.56	.171	.017	**DP1080-17**	A3134-017-24A	**DP1080-17SS**	A1334SS017-24A
#10	.75	.196	.020	**DP1085-20**	A3235-020-24A	**DP1085-20SS**	A3235SS020-24A
#10	.75	.196	.028	**DP1085-28**	A3235-028-24A	**DP1085-28SS**	A3235SS028-24A
1/4	.81	.255-.260	.020	**DP1095-20**	A3475-020-24A	**DP1095-20SS**	A3475SS020-24A
1/4	.81	.255-.260	.028	**DP1095-28**	A3475-028-24A	**DP1095-28SS**	A3475SS028-24A

NAS1515 NYLON WASHER 101 NYLON 6/6
NAS549 FIBER WASHER Insulating, Electrical MIL-F-1148-CH

NAS1515	SIZE	ID	OD	T	NAS549
-H-02L	**#2**	.105	.250	.031	**FL3**
-H-02	**#2**	.105	.250	.063	**F3**
-H-04L	**#4**	.125	.312	.031	**FL4**
-H-04	**#4**	.125	.312	.063	**F4**
-H-06L	**#6**	.149	.375	.031	**FL6**
-H-06	**#6**	.149	.375	.063	**F6**
-H-08L	**#8**	.174	.375	.031	**FL8**
-H-08	**#8**	.174	.375	.063	**F8**
				.090	**FH10**
-H-3L	**#10**	.203	.438	.031	**FL10**
-H-3	**#10**	.203	.438	.063	**F10**
-H-4L	**1/4**	.265	.500	.031	**FL416**
-H-4	**1/4**	.265	.500	.063	**F416**
-H-5L	**5/16**	.328	.562	.031	**FL516**
-H-5	**5/16**	.328	.562	.063	**F516**
-H-6L	**3/8**	.390	.625	.031	**FL616**
-H-6	**3/8**	.390	.625	.063	**F616**



Copyright 2007 All Rights Reserved